

23001 – blue
23002 – yellow

Poliesterski kit SOFT

CODE

NAME

PRODUCT

Poliesterski kit SOFT is two-component polyester putty for carbody of personal and commercial vehicles. Fine body filler easy to work, characterized by good shaping properties in any required thickness.

APPLICATION

The substrate must be clean, dry, degreased and matted. Stir *Poliesterski kit SOFT*, add 2 to 3% hardener by weight, and then stir again. Apply within 5 minutes at 20 ° C. Higher temperatures can shorten the implementation time and accelerate drying.

NOTE

Using too much hardener can cause discoloration on the surface. Should not be used at temperatures below 15°C.

TECHNICAL INFORMATIONS

Characteristic	Measures	Variance
Colour	Blue, yellow	//
Drying time (20°C, 50% RH)	~ 16 - 30 min	//
Hand sanding (dry)	P150 – P320	//
Machine sanding (dry)	P150 – P320	//
Application temperature	20°C	//
V.O.C. category B(b) maximum value 250 g/L	This products contains less then 249 g/L	
Storage	12 months from the date of production in a dark and dry place at temperature from 5 to 25°C	
Packaging	Cans 1,8 Kg with 40 g hardener	

SAFETY MEASURES

Look at Technical data sheet.

ADR CLACIFICATION

Look at Technical data sheet

RESPONSIBILITY STATEMENT

The information shown in these sheets is given in good faith as being true and although every effort of verification has been made before use, we cannot accept responsibility for any inaccuracy. THIS PRODUCT IS FOR THE PROFESSIONAL PAINTING BY QUALIFIED PERSONNEL