

28011 – grey, 1 KG

# Masa za brtvljenje

SEAM SEALANT

CODE

NAME

## PRODUCT

*Masa za brtvljenje* is a sealant based on a mixture of elastomeric rubbers in solvent that hardens at room temperature. The product cures into a strong but flexible sealant, does not crack even at high temperatures. It shows excellent adhesion on rough or painted metals. *Masa za brtvljenje* is brushable and overpaintable after tack dry. Used in car body repair and car industry to seal welded, bolted and overlapped metal sheet joints.

## METHOD OF USE

To clean surfaces use synthetic diluent. Spread the product with bristle brush. Application temperature should be from +5 to +35°C

## TECHNICAL INFORMATIONS

Property	Value and UM	Tolerance
Chemical base	elastomers	
Colour	Grey	//
Aspect	Creamy thixotropic paste	
Density	1,17±0,02 g/cm <sup>3</sup>	
Solid content	>70%	
Tack free time (23°C, 55% RH)	4 min	N / A
Through curing speed (23°C, 50% RH)	~ 2 mm in 24 hrs	N / A
Application temperature	+5° - +35°C	
Shelf life	18 months from production date stored in original closed packaging, in cool dry place at temperature less then +30°C	
Packaging	Cans of 1 KG	

## SAFETY PRECAUTIONS

Please see our latest EC safety data sheet for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC safety data sheet for details.

## DISCLAIMER

The information shown in these sheets is given in good faith as being true and although every effort of verification has been made before use, we cannot accept responsibility for any inaccuracy. THIS PRODUCT IS FOR THE PROFESSIONAL USE BY QUALIFIED PERSONNEL